

# Romaccon Snap Clamps


## ROMACCON

Romaccon Snap Clamps are used for the permanent repair of damaged pipes above ground


for water, gas and petrochemical fluids



Following types of damage can be repaired:



cracks / local damage



Pit holes

### Application:

Snap Clamps provide a fast and economic repair to small damages in pipes up to ND 300.

They are applied on board of ships and by plumbers for repairs above ground.

The rubber partially covers the inside of the band and allows the repair of small holes caused by corrosion or frost.

The clamps can be used on following pipe types:

- Ductile Iron (DI)
- Copper
- Cast Iron (CI)
- Steel (St.)

### Pressure ratings:

- Pipe OD 21–111 mm 20 bar
- Pipe OD 112–229 mm 10 bar

Maximum pressure for gas pipes is 4 bar (for all POD up to incl. 229 mm)

### Available sizes:

Snap Clamps are available for pipes up to ND 300 and length 75, 150 and 225 mm.

We will send you a pricelist with all available ranges on request.

For larger ranges we can supply double band snap clamps.

### Material specification:

- Lugs: ductile iron GGG 40 acc. to Din 1693 or malleable iron GTW 40 acc. to Din1692, surface sheradized with 15 microns zinc.
- Band: stainless steel acc. to AISI 304
- Bolts: Special mushroom head square neck bolts. Bolt size M10 up to 2" and M12 for larger sizes. Material acc. to class 4.6, surface galvanized with 5 microns zinc.
- Hexagon nuts: acc. to Din 934 class 5, surface galvanized with 5 microns zinc.
- Washer: acc. to Din125a, surface galvanized with 5 microns zinc.
- Rubber (standard): waffled NBR; acc. to ISO gas and water pipelines.



Romaccon has been certified to ISO 9001:2000 by Tuv